

Tubular Rack System

The adjustable tubular rack system offers easy, flexible installation with advanced multi-voltage water-resistant power supply featuring the Triatomic lifetime power supply warranty. This system effectively kills mold, bacteria, and viruses in HVAC equipment. You will save energy by keeping the system cleaner, lowering maintenance costs and reducing chemical exposure to maintenance workers.

32"- 46"- 60" UV-C Lamps Available



Optional mounting magnet

Lifetime

water-resistant power supply


FEATURES

- Allows for UVC light to be radiated throughout the entire AHU
- Designed to be built onsite for endless size combinations for exact fit
- High quality water-resistant lamps
- Water-resistant power supply, normal or high output
- Triatomic lifetime power supply warranty
- Includes all necessary mounting hardware except 0.5" EMT conduit
- Optional stainless steel tubing available

BENEFITS

- · Kills mold, bacteria, and viruses in the HVAC system
- Saves energy by keeping components cleaner
- Lowers maintenance costs reduced cleanings
- Reduces worker exposure to chemicals
- Cost effective

UV-C light supresses microbial growth on HVAC coils and surrounding areas



Lamp Options



1 Year Lamp Standard Output



2 Year Lamp Standard Output



1 Year Lamp High Output



Manufactured by Triatomic Environmental, Inc. **WWW.FRESHAIREUV.COM** sales@freshaireuv.com





FRESH-AIRE UV. COMMERCIAL SERIES TUBULAR RACK SYSTEM

- Sterilizes microbial growth inside the air system
- Kills airborne germs as they pass by
- Improves indoor air quality
- Chemical-free disinfection
- Reduces maintenance costs

| Specifications | | |
|------------------------|--|--|
| Dimensions | S-D Power supply: 8.75"L x 3.75"W x 2.5"H T-Q Power supply: 13"L x 3.75"W x 2.5"H 32" Lamp & APCO Module: 36" L x 4.5"H 3"D Lamp: 32"L x 0.875 Dia. 60" Lamp & APCO Module: 64"L x 4.5"H 3"D Lamp: 60"L x 0.875 Dia. | |
| Kit includes | Remote power supply, 10' lamp cable, 6' power cord, UV lamp, mounting hardware and view port, 0.5" EMT conduit not included | |
| Electrical | 120-277 VAC 50/60 Hz | |
| Power Supply | TUVCPS-32S & TUVCPS-32D Current 0.94 A/120V Thru 0.40 A/277V TUVCPS-32T & TUVCPS-32Q Current: 1.88 A/120V Thru 0.80 A/277V TUVCPS-60S Max Current 1.24 A/120V TUVCPS-60D Max Current 2.48 A/120V TUVCPS-H120S Max Current 1.15 A/120V TUVCPS-H230S Max Current .57 A/230V TUVCPS-H120D Max Current 2.3 A/120V TUVCPS-H230D Max Current 1.14 A/230V | |
| Lamps | 1 Year Standard Output (Quartz hot filament) 2 Year Standard Output (Shielded quartz hot filament with filament guard) UV spectrum 254 NM Teflon® coating available | |
| TUVCL-132 TUVCL-232 | 32″ 1 Year - 165 μW/cm2 @ 1 meter, 44 Watts 32″ 2 Year - 165 μW/cm2 @ 1 meter, 44 Watts | |
| TUVCL-132 HO | 32″ 1 Year - 300 μW/cm2 @ 1 meter, 80 Watts | |
| TUVCL-146 TUVCL-246 | 46" 1 Year - 190 μW/cm2 @ 1 meter, 54 Watts 46" 2 Year - 190 μW/cm2 @ 1 meter, 54 Watts | |
| TUVCL-160 TUVCL-260 | 1 Year - 250 μW/cm2 @ 1 meter, 68 Watts 2 Year - 250 μW/cm2 @ 1 meter, 68 Watts | |



| Part Numbers | | |
|---|--|--|
| 1 Year 32" Standard Output | Power Supply Included | |
| TUVC-TRS-132S (single) TUVC-TRS-132D (dual) TUVC-TRS-132T (triple) TUVC-TRS-132Q (quad) | TUVCPS-32S TUVCPS-32D TUVCPS-32T TUVCPS-32Q | |
| 2 Year 32" Standard Output | Power Supply Included | |
| TUVC-TRS-232S (single) TUVC-TRS-232D (dual) TUVC-TRS-232T (triple) TUVC-TRS-232Q (quad) | TUVCPS-32S TUVCPS-32D TUVCPS-32T TUVCPS-32Q | |
| 1 Year 32" High Output | Power Supply Included | |
| TUVC-TRS-132S-H0120 (single 120 VAC) TUVC-TRS-132S-H0230 (single 230 VAC) TUVC-TRS-132D-H0120 | TUVCPS-H120S TUVCPS-H230S | |
| (dual 120 VAC) TUVC-TRS-132D-HO230 (dual 230 VAC) | TUVCPS-H120D TUVCPS-H230D | |
| 1 Year 46" Standard Output | Power Supply Included | |
| TUVC-TRS-146S (single) TUVC-TRS-146D (dual) | TUVCPS-60S TUVCPS-60D | |
| 2 Year 46" Standard Output | Power Supply Included | |
| TUVC-TRS-246S (single) TUVC-TRS-246D (dual) | TUVCPS-60S TUVCPS-60D | |
| 1 Year 60" Standard Output | Power Supply Included | |
| TUVC-TRS-160S (single) TUVC-TRS-160D (dual) | TUVCPS-60S TUVCPS-60D | |
| 2 Year 60" Standard Output | Power Supply Included | |
| TUVC-TRS-260S (single) TUVC-TRS-260D (dual) | TUVCPS-60S TUVCPS-60D | |



